

AVOCENT® MATRIX HIGH PERFORMANCE KVM

A fusion of performance and speed for new levels of content creation, production and delivery



Revolutionary centralized software management system

Digital and analog video support

PoE-powered transmitters

Multi-colored back lit LCD allows at-a-glance status identification of transmitters and receivers

Instant switching - less than half a second

USB 2.0 single line speed is up to 66% faster than the competition

Extendable Architecture

Design 9-0.6 (t0)6.8o (sh)2.9u(g)2.7p(e)e9-0.6o(sh)2.5 (-26-p.9t c(i)-0.7u(g)0.6rr(t0)3.7 (e))2.9n(r)1.1 (e)T /Spn ActualTextEFF09>BDC()9TJEM

Specifications

Avocent® Matrix MXT5110

Mechanical

Dimensions (DxWxH):

6.2 x 4.75 x 1.21 in.

Weight: 1.4 lbs. / 0.64kgs

Ports/Connectors

USB: 1 x Type B

Microphone: 1 x 3.5mm stereo

Speaker: 1x 3.5mm stereo

Video: 1 x DVI-D or 1 x VGA

Direct Connect: 1 x 8-pin modular

Power Supply

N/A

Operating Temperature

0° C to 40° C

Avocent Matrix MXR5110

Mechanical

Dimensions (DxWxH): 4.9 x 8 x 1.21

Weight: 1.6 lbs. / 0.73kgs

Ports/Connectors

USB: 6 x Type B (2 front, 4 rear)

Microphone: 1 x 3.5mm stereo