

# BE325-UK

400-1500VA

Peace of mind from the world's most trusted UPS.

## PRODUCT FEATURES

- Back up and protect your hardware and data during power outages, surges and spikes.
- Protect secondary electronics from surges and spikes without reducing battery power used to run primary electronics during an outage.
- Periodic battery self-test ensures early detection of a battery that needs to be replaced.
- Provides early-warning fault analysis on batteries enabling timely preventive maintenance
- Maximizes battery performance, life, and reliability through intelligent, precision charging.
- Easy recovery from overloads; no need to replace a fuse.
- Provides notification of changing utility power and UPS power conditions
- Quickly understand unit and power status with visual indicators.
- Ensures the product has been tested and approved to work safely with the connected service provider
- equipment and within the specified environment.
- Reserves power capacity and run time for connected equipment that require UPS battery back-up while providing surge only protection for less critical equipment
- Provides protection of connected equipment from power surges on the data lines.
- Provides peace of mind by providing professional data recovery services in the event data is lost due to the failure of the unit.
- Easy recovery from overloads; no need to replace a fuse.

# Technical Specifications

BE325-UK	
Output	
Output Power Capacity	185 Watts / 325 VA
Max Configurable Power	185 Watts / 325 VA
Nominal Output Voltage	230V VA
Output Frequency (sync to mains)	50 Hz
Topology	Standby
Waveform Type	Stepped approximation to a sinewave
Output Connections	(2)BS 1363(Battery Backup) (2)BS 1363(Surge Protection)
Input	
Nominal Input Voltage	230V
Input Frequency	50 Hz +/- 3 Hz
Input Connections	British BS1363A(Surge Protection)
Cord Length	1.83 meters
Input voltage range for main operations	180 - 260V
Batteries & Runtime	
Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	24 hour(s)
Replacement Battery	RBC47
RBC&#153; Quantity	1
Communications & Management	
Control panel	LED Status display with On Line : On Battery
Audible Alarm	Alarm when on battery : distinctive low battery alarm
Surge Protection and Filtering	
Surge energy rating	300 Joules
Filtering	--
Data Line Protection	RJ-11 Modem/Fax/DSL protection (two wire single line)
Physical	
Maximum Height	115.00
Maximum Width	360.00
Maximum Depth	95.00
Net Weight	4.00 KG
Shipping Weight	4.60 KG
Shipping Height	153.00
Shipping Width	465.00
Shipping Depth	116.00
Master Carton Units	1.00
Master Carton Dimensions (Length x Width x Height)	9.65 inches
Master Carton Weight	41.36 lbs.
Color	Charcoal KG
SCC Codes	1073130421115 7
Units per Pallet	160.00
Environmental	
Operating Environment	0 - 40
Operating Relative Humidity	5 - 95
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45
Storage Relative Humidity	5 - 95
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	45.00 dBA
Online Thermal Dissipation	31.00 BTU/hr
Conformance	
Regulatory Approvals	CE, EN 50091-1, EN 50091-2
Standard Warranty	2 years repair or replace

BE325-UK

Equipment protection policy	Lifetime : 75000 Euros, Lifetime : 35000 GBP
Sustainable Offer Status	
REACH	REACH: Contains No SVHCs
PEP	Available in Documentation tab
EOLI	Available in Documentation tab
Battery Directive	Compliant
Other Environmental Compliance	China RoHS