

# 2914 Series

## PCI Express Gigabit Network Adapters with Wake-on-LAN Support

Allied Telesis 2914 Series Network Adapters feature a PCI Express (PCIe x1) design, combining maximum bandwidth and PCI bus efficiency with the benefits of low power consumption. The 2914 is the only Gigabit 1000SX fiber adapter with Wake-on-LAN (WoL) support completely through the PCI bus.

### High reliability

The Allied Telesis 2914 Series Gigabit interface includes a comprehensive Microsoft Windows utility which performs detailed tests, diagnostics and analysis.

### Advanced manageability

Priority queuing allows users to set up the network based on their individual needs. A comprehensive diagnostics and configuration software suite provides system administrators and engineers with a powerful tool to analyze the adapter card and check specific data.

### Wake-on-LAN (WoL)

WoL allows users to remotely power on or wake up an otherwise unavailable computer from a remote location. WoL is a versatile technique that allows computers to be deactivated when not required.

When WoL is enabled, the computer maintains power to the network adapter, and continues to process network packets. When a valid WoL packet is detected the network adapter powers on or resumes the computer.

Effective use of WoL allows system administrators or users to turn computers on remotely, for patch management remote support and remote access. WoL has the potential to greatly increase the use of low-power modes and energy-saving techniques.

## Specifications

### Management Features

Windows Management Instrumentation (WMI)  
PXE 2.1  
SNMP  
PCI Express v1.1

### Bus Type

PCIe x1

### Ethernet

IEEE 802.1p	Quality of Service
IEEE 802.1Q	VLANs
IEEE 802.2	LLC
IEEE 802.3ac	MAC
IEEE 802.3x	Flow control auto-negotiation
IEEE 802.3z	1000 Base-X
IEEE 802.3ad	Link aggregation

### Drivers

Windows 10, 64- or 32-bit  
Windows 8, 64- or 32-bit  
Windows 7, 64- or 32-bit  
Windows Vista, 64- or 32-bit  
Windows Server 2012 R2, 64-bit  
Windows Server 2012, 64-bit  
Windows Server 2008 R2, 64- or 32-bit  
Windows Server 2008, 64- or 32-bit  
Linux 2.6

### Interface Type and Connector

100/1000MB SFP Slot  
Optical sensitivity Depends on SFP  
Output optical power Depends on SFP  
Wavelength Depends on SFP

1000SX/SC connector  
Optical sensitivity -17 dBm  
Output optical power -9.5/-4 dBm  
Wavelength 850 nm

1000SX/LC connector  
Optical sensitivity -17 dBm  
Output optical power -9.5/-4 dBm  
Wavelength 850 nm

### Status Indicators

LED	On	Link up
	Off	Link down
	Blinking	Activity

## Key Features

### Management Software

- ▶ VLAN support
- ▶ Link aggregation LACP
- ▶ Link aggregation smart switch
- ▶ Failover

### Advanced Properties

- ▶ WoL support
- ▶ Jumbo frames up to 9.6KB
- ▶ Secure transmissions
- ▶ PCI Express (PCIe x 1)
- ▶ Smart Load Balancing (SLB) and failover
- ▶ Link aggregation (IEEE 802.3ad)
- ▶ Generic trunking (FEC/GEC) / IEEE 802.3ad-draft static
- ▶ UEFI network boot
- ▶ IEEE 802.1x flow control
- ▶ SNMP
- ▶ IPv6
- ▶ Low-profile and standard height brackets included
- ▶ Vista, 7, 8, 10, and Linux

### Power

Power consumption	AT-2914SX/SC 1.7 watt (typical) AT-2914SX/LC 1.5 watt (typical)
Signaling voltage	3.3V

### Environmental Specifications

Operating temperature	0°C to 50°C (32°F to 122°F)
Relative humidity	5% to 90% (non-condensing)
Storage temperature	-25°C to 70°C (-13°F to 158°F)

### Physical characteristics

Dimensions (W x H)	8.8 cm x 6.9 cm (3.5 in x 2.7 in)
Weight	0.068 kg (0.13 lb)

### Compliance

RoHS  
UL  
FCC/EN55022 Class A  
TUV  
EN55024  
CE  
C-TICK  
VCCI

### Ordering Information

#### Single Port Models

##### AT-2914SX/SC-xxx

1000SX SC PCI Express x1 network adapter

##### AT-2914SX/LC-xxx

1000SX LC PCI Express x1 network adapter

##### AT-2914SP-xxx

100MB or 1000MB SFP x 1 adapter card

Where xxx = 001 for single pack  
901 for single pack, Federal and Government

Ships with low-profile bracket attached to network adapter.  
Standard bracket is included in packaging.



NETWORK SMARTER

**North America Headquarters** | 19800 North Creek Parkway | Suite 100 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895

**Asia-Pacific Headquarters** | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830

**EMEA & CSA Operations** | Incheonweg 7 | 1437 EK Rozenburg | The Netherlands | T: +31 20 7950020 | F: +31 20 7950021

[alliedtelesis.com](http://alliedtelesis.com)

© 2017 Allied Telesis, Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners.  
617-000609 RevB