



by Schneider Electric

Easy PDU Metered Rack Power Distribution Unit

Overview

EPDU1116M, EPDU1132M

The APC by Schneider Electric Easy PDU, Metered Rack Power Distribution Unit may be used as a stand-alone, network-manageable power distribution device. The Easy PDU provides real-time remote monitoring of connected loads. User-defined alarms warn of potential circuit overloads. You can manage your Easy PDU through its Web User Interface (Web UI), or Simple Network Management Protocol (SNMP).

Display Interface. The liquid crystal display (LCD) and function button allow you to monitor phase voltage, current, and power factors of attached devices. Remote communication can be established through the network port. Environment is monitored through the temperature and humidity (T/H) port.

Outlets.

EPDU1116M: Eighteen (18) C13 10A outlets and three (3) C19 16A outlets

EPDU1132M: Bank 1: Ten (10) C13 10A outlets and two (2) C19 16A outlets

Bank 2: Ten (10) C13 10A outlets and two (2) C19 16A outlets

Power cord.

EPDU1116M: The power cord is 3 m (9.8 ft) in length.


EPDU1132M: The power cord is 3 m (9.8 ft) in length.

Mounting.


Brackets: The Rack PDUs can be mounted to a rack using the two (2) brackets and mounting hardware provided.

Toolless Mounting: Two (2) mounting pegs are installed on the back sides of the Rack PDUs for 0U mounting capability in a rack or enclosure.

EPDU1116M



EPDU1132M



Specifications

| | EPDU1116M | EPDU1132M |
|--|--|--|
| Electrical | | |
| Nominal Input Voltage | 200 - 240 VAC 1 PHASE | |
| Maximum Input Current (Phase) | 16A | 32A |
| Input Frequency | 50/60Hz | |
| Input Connection | IEC309 16A | IEC309 32A |
| Output Voltage | 200 - 240 VAC 1 PHASE | |
| Output Connections | Eighteen (18) C13 Max. output current 10A Three (3) C19 Max. output current 16A | Bank 1: Ten (10) C13 Max. output current 10A Two (2) C19 Max. output current 16A Bank 2: Ten (10) C13 Max. output current 10A Two (2) C19 Max. output current 16A |
| Circuit Breakers | None | Two (2) 16A 1-pole hydraulic-magnetic circuit breakers |
| Physical | | |
| Dimensions (H x W x D) | 902 x 62 x 44.4 mm (35.5 x 2.44 x 1.74 in) | 1175 x 62 x 44.4 mm (46.25 x 2.44 x 1.74 in) |
| Input power cord length | 3 m (9.8 ft) | 3 m (9.8 ft) |
| Shipping dimensions (H x W x D) | 1320 x 160 x 110 mm (52.0 x 6.30 x 4.33 in) | 1320 x 160 x 110 mm (52.0 x 6.30 x 4.33 in) |
| Weight/Shipping weight | 2.2 kg (4.85 lb)/ 3.0 kg (6.61 lb) | 3.72 kg (8.20 lb)/ 4.48 kg (9.87 lb) |
| Environmental | | |
| Maximum elevation (above MSL) Operating/Storage | 0–3000 m (0–10,000 ft) / 0–15000 m (0–50,000 ft) | |
| Temperature: Operating/Storage | –5 to 45°C (23 to 113°F)/ –25 to 65°C (–13 to 149°F) | |
| Humidity: Operating/Storage | 5–95% RH, non-condensing | |
| Compliance | | |
| EMC verification | CE EN55035, EN55032, EN55024 | |
| Safety verification | CE, TUV, EN/IEC62368-1 | |
| CE EU Contact Address | Schneider Electric, 35 rue Joseph Monier 92500 Rueil Malmaison France | |
| Environmental | RoHS & Reach | |

Customer support and warranty information are available on the APC by Schneider Electric website, www.apc.com.

© 2019 APC by Schneider Electric. APC and the APC logo are owned by Schneider Electric S.E. All other trademarks are property of their respective owners.

990-6294
11/2019