

Category 5e Vertical Wall Outlet

The Connectix 4000 Series offers Enhanced Category 5 performance in a High-Density package. The Connectix 4000 Series is extremely quick and easy to install; just attach the base plate, snap in the PCB, punch down the cables and install the cover. Gone are the problems of installing modules into a faceplate and pushing excess wires into a back box.

The 4000 Series Outlets have been designed for direct wall mounting with top entry mini trunking. In addition, they fit on a standard back box to provide maximum mounting flexibility. The position of the sockets on the Vertical Outlet allow for a compact installation without protruding leads.

Features & Benefits

- High Density, single gang unit
- Available in a 2 or 4 port version
- Enhanced Category 5 performance
- No protruding leads
- Designed for direct wall mounting
- Custom logo service available



Product Specifications		
Width (mm)		87
Depth (mm)		27
Height		87
Number of Ports		2 or 4
Material	ABS thermoplastic resin, with grade UL94 VO at 1.5 mm flame retardancy	
Finish		High Gloss
IDC Colour		Code IDC colour code to T568B
IDC Blocks		4-way industry standard IDC blocks
PBC		1.6mm double sided PTH boards
Conforms To		ANSI/TIA-568-C

Ordering Information		
Product Description		Part Number
Cat 5e Vertical Wall Outlet- 2 Way		008-001-011-03
Cat 5e Vertical Wall Outlet - 4 Way		008-001-011-01