

# BE400-UK

400-1500VA

Peace of mind from the world's most trusted UPS.

## PRODUCT FEATURES

- Back up and protect your hardware and data during power outages, surges and spikes.
- Protect secondary electronics from surges and spikes without reducing battery power used to run primary electronics during an outage.
- Periodic battery self-test ensures early detection of a battery that needs to be replaced.
- Provides early-warning fault analysis on batteries enabling timely preventive maintenance
- Maximizes battery performance, life, and reliability through intelligent, precision charging.
- Easy recovery from overloads; no need to replace a fuse.
- Provides notification of changing utility power and UPS power conditions
- Quickly understand unit and power status with visual indicators.
- Ensures the product has been tested and approved to work safely with the connected service provider
- Reserves power capacity and run time for connected equipment that require UPS battery back-up while providing surge only protection for less critical equipment
- Provides protection of connected equipment from power surges on the data lines.
- Provides peace of mind by providing professional data recovery services in the event data is lost due to the failure of the unit.
- Easy recovery from overloads; no need to replace a fuse.

# Technical Specifications

| BE400-UK   |  |
|--|--|
| <b>Output</b>                                      |  |
| Output Power Capacity                              | 240 Watts / 400 VA   |
| Max Configurable Power                             | 240 Watts / 400 VA   |
| Nominal Output Voltage                             | 230V VA  |
| Topology   | Standby  |
| Waveform Type                                      | Stepped approximation to a sinewave  |
| Output Connections                                 | (4)BS 1363(Battery Backup) (4)BS 1363(Surge Protection)  |
| <b>Input</b>                                       |  |
| Nominal Input Voltage                              | 230V   |
| Input Frequency                                    | 50/60 Hz   |
| Input Connections                                  | British BS1363A(Surge Protection)  |
| Cord Length  | 1.83 meters  |
| <b>Batteries &amp; Runtime</b>                     |  |
| Battery Type                                       | Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof                                     |
| Typical recharge time                              | 16 hour(s)   |
| Replacement Battery                                | APCRBC106  |
| RBC&#153; Quantity                                 | 1  |
| <b>Communications &amp; Management</b>             |  |
| Control panel                                      | LED Status display with On Line : On Battery   |
| Audible Alarm                                      | Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm                               |
| <b>Surge Protection and Filtering</b>              |  |
| Surge energy rating                                | 310 Joules   |
| Filtering  | Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449       |
| Data Line Protection                               | Analog phone line for phone/fax/modem/DSL (RJ-11 connector), Network line - 10/100 Base-T Ethernet (RJ-45 connector) |
| <b>Physical</b>                                    |  |
| Maximum Height                                     | 86.00  |
| Maximum Width                                      | 230.00   |
| Maximum Depth                                      | 285.00   |
| Net Weight   | 5.40 KG  |
| Shipping Weight                                    | 5.60 KG  |
| Shipping Height                                    | 132.00   |
| Shipping Width                                     | 300.00   |
| Shipping Depth                                     | 366.00   |
| Master Carton Units                                | 2.00   |
| Master Carton Dimensions (Length x Width x Height) | 380  |
| Master Carton Weight                               | 12.20 KG   |
| Color  | Charcoal   |
| SCC Codes  | 1073130423340 1  |
| Units per Pallet                                   | 48.00  |
| <b>Environmental</b>                               |  |
| Operating Environment                              | 0 - 40   |
| Operating Relative Humidity                        | 0 - 95   |
| Operating Elevation                                | 0-15000 meters   |
| Storage Temperature                                | 0 - 40   |
| Storage Relative Humidity                          | 0 - 95   |
| Storage Elevation                                  | 0-15000 meters   |
| Audible noise at 1 meter from surface of unit      | 45.00 dBA  |
| <b>Conformance</b>                                 |  |
| Regulatory Approvals                               | BSI 1363, CE   |
| Standard Warranty                                  | 2 years repair or replace, 3 years repair or replace for European Union countries                                    |
| Equipment protection policy                        | Lifetime : 50000 GBP   |

## BE400-UK

### Sustainable Offer Status

|                                |                                |
|--------------------------------|--------------------------------|
| REACH                          | REACH: Contains No SVHCs       |
| PEP                            | Available in Documentation tab |
| EOLI                           | Available in Documentation tab |
| Battery Directive              | Compliant                      |
| Other Environmental Compliance | China RoHS                     |