

PCI Express AC1200 Dual Band Wireless-AC Network Adapter - PCIe 802.11ac WiFi Card

StarTech ID: PEX867WAC22



The PEX867WAC22 PCI Express AC1200 Wireless Network Adapter lets you add dual-band Wireless-AC connectivity to a desktop computer through a PCIe slot.

With increased demand on network resources, this Wireless-AC adapter gives you exceptional speed and range for your office or home wireless network when paired with an 802.11ac router. This dual-band WiFi adapter supports maximum data rates of up to 867 Mbps on the 5GHz band (3x the speed of Wireless-N), plus up to 300 Mbps on the 2.4GHz band, making it the perfect solution for applications like HD video streaming, online conferencing, file transfers and gaming.

This versatile PCIe wireless card features a 2T2R (2 transmitter, 2 receiver) detachable antenna design, with an included magnetic antenna stand that can easily be mounted to the top or side of your PC case. Plus, the controller card is equipped with a standard profile bracket and includes a low-profile/half-height bracket for installation in small form-factor computers. To integrate with all of your networking devices, the adapter is also backward compatible with 802.11a/b/g/n networks.

Backed by a StarTech.com 2-year warranty, with free lifetime technical support.

Applications

- Replace or upgrade the wireless capabilities of your desktop system to the latest standard
- Connect to the less congested 5 GHz WiFi band to avoid interference from common wireless devices such as cordless phones
- Conference online, transfer files, stream HD video or game without lag, through faster wireless performance



Features

- Wireless AC1200 compatible (867 Mbps + 300 Mbps)
- Compliant with 802.11 a/b/g/n/ac standards
- Dual band 2.4 / 5 GHz support (802.11ac is 5 GHz only)
- PCI Express host interface
- 2 Transmitter/2 Receiver (2x2:2) antenna configuration
- Included magnetic antenna stand for side-mounting on your PC case
- Supports WEP (64-128-bit), WPA and WPA2 wireless security
- Supports WMM Quality of Service
- Supports Soft AP mode
- Configured with standard profile bracket, low profile/half-height bracket included





Technical Specifications

Warranty 2 Years

Interface Wireless Ethernet

Bus Type PCI Express

Card Type Standard Profile (LP bracket incl.)

Antenna Configuration 2x2:2 (TxR:S)

Industry Standards IEEE 802.11ac Draft 2.0, IEEE 802.11n, IEEE 802.11g, IEEE 802.11a, IEEE

802.11b

Chipset ID Realtek - RTL8812AE
Connector Type(s) 1 - PCI Express x1 Male

Connector Type(s) 1 - Wireless AC (IEEE 802.11ac)

External Ports 2 - RP-SMA (Coax; Reverse Polarity SubMiniature A) Female

Maximum Data Transfer Rate 867 Mbps (5 GHz)

300 Mbps (2.4 GHz)

Full Duplex Support Yes

Frequency Range 2.400 ~ 2.484GHz

5.180 ~ 5.850GHz

Security Features WEP Data Encryption
Security Features WPA Data Encryption

Security Features TKIP/AES

OS Compatibility Windows® 8 / 8.1 (32/64bit), 7 (32/64), Vista(32/64), XP(32/64)

Windows Server® 2012, 2008 R2, 2003(32/64)

System and Cable

Requirements

Available PCI Express x1 (or higher) slot

Product Length 3.4 in [87 mm]
Product Width 0.7 in [18 mm]
Product Height 4.7 in [120 mm]
Product Weight 2.9 oz [82 g]
LED Indicators 1 - Link / Act

Operating Temperature 0°C to 60°C (32°F to 140°F) Storage Temperature 0°C to 70°C (32°F to 158°F)

Humidity 10~90% RH Shipping (Package) Weight 13.7 oz [388 g]

Included in Package 1 - PCI Express Wireless AC Card Included in Package 2 - 5 dBi Dual Band Antennas



Hard-to-find made easy®

Spec Sheet

Included in Package 1 - Antenna Stand

Included in Package 1 - Low Profile Bracket

Included in Package 1 - Driver CD

Included in Package 1 - Instruction Manual

Certifications, Reports and Compatibility











