



Elite Phone Host Panel

Features & Benefits

- High density 12 or 24 ports in 1u
- Custom logo service available
- Available in a range of colours
- RJ45 to RJ45/IDC connection
- 4 outlets from 1 input

Specification

| | |
|---------------|---|
| Width | 483mm (19") |
| Depth | 30mm |
| Height | 1u (44mm) |
| Material | Mild steel sheet CR4 to BSEN 10130-1999 DC01 Plastic inserts ABS thermoplastic resin with grade UL94 V0 at 1.5mm flame retardancy |
| Finish | Black powder coat B56496 |
| Socket Labels | 9mm numbered card with acetate cover |
| RJ45 Sockets | Unshielded vertical jacks |
| IDC Block | 4 way industry standard IDC blocks |
| PCB | Groups of 4 identical circuits on 1.6mm double sided PTH boards |
| Conforms to | TIA/EIA-568-C Enhanced Category 5 Specification |

Ordering Information

| Product Description | Part Number |
|-------------------------------|----------------|
| 12 Way Elite Phone Host Panel | 009-001-016-15 |
| 24 Way Elite Phone Host Panel | 009-001-016-16 |

The Connectix Elite Phone Host Panel has been designed to allow for integration of phone lines into the structured cabling network. It comprises of separate units that have a single input at the rear which is distributed to 4 outputs on the front.

The Elite Phone Host Panel allows 4 extensions to share a single phone within each of the units. The units can be connected together giving the option of multiple extensions from a single panel.

The panel has been designed to match all the other panels in the Connectix Elite Panel range ensuring versatility and flexibility.

A 12 port format is available specifically for the Connectix Home Cabling range.

