

AT-2972SX

PCI-Express Fiber Gigabit Interface Card



AT-2972SX

PCIe x 1 (channel) fiber Gigabit interface card

More Bandwidth with PCI-Express Interface

The PCI-Express (PCIe) design gives you the maximum possible bandwidth and bus efficiency. Other benefits are capability and low power consumption.

High Reliability

The AT-2972SX Gigabit interface card comes with a comprehensive Microsoft Windows utility that performs detailed tests, diagnostics and analysis.

Advanced Manageability

The priority queuing offered by the AT-2972SX can help you set-up your network based on your own needs. The comprehensive diagnostics and configuration software suite provides system administrators and engineers with a profound tool to analyze the network interface card to check specific data.

Key Features

Management Software

- VLAN support
- Link aggregation LACP
- Link aggregation smart switch
- Failover

Advance Properties

- Jumbo frames
- Checksum offloading
- Secure transmissions
- PCI-Express
- Windows Vista
- IEEE 802.1x flow control
- IEEE 802.1p-based traffic prioritization
- PXE remote boot support
- Low-profile and standard height brackets included
- Microsoft certified drivers
- RoHS compliant
- Load balancing
- CPU task offload
- TCP segmentation
- SNMP
- IPv6
- Compliant with the Trade Agreement Act

AT-2972SX | PCI-Express Fiber Gigabit Interface Card

Specifications

Management Features

WMI
ACPI 1.1
PXE 2.1 Boot ROM
SNMP

Bus Type

PCIe x1

Ethernet Standards

IEEE 802.1p	Quality of Service
IEEE 802.1Q	VLANs
IEEE 802.2	LLC
IEEE 802.3ac	MAC
IEEE 802.3az	1000SX
IEEE 802.3x	Flow control, auto-negotiation
IEEE 802.3z	1000X
IEEE 802.3ad	Link aggregation

Drivers Supported

Vista
Vista 64-bit
Windows XP
Windows XP 64-bit
Windows 2003
Windows 2003 64-bit
Windows 2000
NDIS2
NetWare 6.x
Linux 2.4
Linux 2.6

Available

Windows NT 4
Solaris x86
Solaris Sparc 32-bit
Solaris Sparc 64-bit
NetWare 5.x

Compliance

RoHS
UL
FCC/EN55022 Class B
TUV
EN55024
CE
C-TICK
VCCI

Connectors

LC
Optical input power (min) -17dBm
Transmit optical power (min/max) -9.5/-1.5dBm

Environmental Specifications

Operating temperature 0°C to 50°C
Storage temperature -25°C to 70°C
Relative humidity 5% to 90% non-condensing

Power

Power consumption 9.2 Watts (max)
Signaling voltage 3.3V

Status Indicators

LED	2 ports
1000	ON 1000Mbps link up OFF 1000Mbps link down
ACT	ON Receiving/transmitting OFF Not receiving/ not transmitting

Physical Characteristics

Dimensions 9.5cm x 6.8cm
(W x H) (3.7") x (2.7")

Weight 0.7kg

Ships with standard bracket attached to interface card.

Low-profile bracket is included in packaging.

Network Type

1000SX

Network Speed

Auto-negotiation

Network Controller

Broadcom BCM 57155

Ordering Information

AT-2972SX-xxx

PCIe x1 (channel) fiber Gigabit interface card

Where xxx = 001 for single pack
020 for 20-pack
901 for single pack, Federal and
Government
920 for 20-pack, Federal and
Government

Ships with standard bracket attached to interface card.

Low-profile bracket is included in packaging.

USA Headquarters | 19800 North Creek Parkway | Suite 200 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895

European Headquarters | Via Motta 24 | 6830 Chiasso | Switzerland | T: +41 91 69769.00 | F: +41 91 69769.11

Asia-Pacific Headquarters | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830

www.alliedtelesis.com

© 2007 Allied Telesis Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000238 Rev D