



## Tool-less Keystone Module

### Features & Benefits

- Quick and easy to install
- Snap-fit to terminate
- Suitable for all standard Keystone applications
- Compact design
- Category 6 hardware performance
- T568A and T568B colour coded wiring terminals

### Specification

Width	16.3 mm
Depth	31.5 mm
Height	21.0 mm
Mounting Hole Size	19.3 mm x 14.7 mm
Material	Polycarbonate/ABS thermoplastic resin with grade UL94 VO at 1.5mm flame retardancy
IDC Labels	Colour coded to T568A and T568B
IDC Blocks	Tool-less IDC mechanism
Conforms to	ANSI/TIA-568-C Category 6 Specification

### Ordering Information

Product Description	Part Number
Cat 6 Tool-less Keystone Module	008-010-010-60
CCS Angled Shuttered Euro Fascia	008-010-010-18

Connectix Tool-less Keystone Modules ensure a quick and easy to terminate installation. The snap-fit to terminate design means that a punch down tool is not required.

They have been designed to be installed into most UK and European Keystone applications, including standard or angled faceplate products, patch panels or surface boxes.

The loading cap is colour coded to T568A and T568B standards to ensure a quick and easy installation.

The module offers a high performance transmission that meets or exceeds Category 6 standards.

