Features & Benefits

- 2 to 24 fibre configurations
- Choice of fibre type and specification
- Rodent proof
- Water resistant
- High tensile strength and crush resistant
- Corrugated Steel Armouring tape
- Suitable for harsh external environments
- Low cost
- 50/125, 62.5/125 & singlemode fibre types

Specifications

Loose Tube Diameter

Outer Jacket Thickness

Cable Outer Diameter LSZH Jacket Conforms to

Jacket Material Black FRNC/LSZH Max. Tensile Strength 1100 N Crush Resistance 6000 N/10 cm Impact Resistance 3 impacts (w/25N.m) Min. Bend Radius 15x cable diameter Min. Bend Radius (Load) 20 x cable diameter Moisture Resistance Passed Compound Flow 30 cm/24hr/70°C passed Temperature Range Installation: -15°C to +50°C Operation: -20°C to +60°C Storage: -30°C to +70°C Standard Put-up Length 2100 m, 4100 m Nominal Weight 87kg/km

The Fibrefox Uni Tube Steel Tape Armoured Cable is suitable for installation in the most demanding, harsh environments. The cable has excellent tensile strength, crush resistance characteristics and is also rodent proof. The cable consists of a central jelly filled tube, with up to twenty four optical fibres inside.

The tube is protected with a water blocking glass yarn and a thick inner corrugated steel tape armour is then applied. A black FRNC/LSZH outer sheath then protects the cable construction and is extremely resistant to the ingress of moisture.

A choice of multimode and singlemode fibre types and specifications are offered ranging from 2, up to 24 fibre configurations.

This tough rugged cable is ideal for all external environments including LAN direct burial, tunnels and heavy-duty ducts.

Ordering Information

Product Description Uni Tube CST OS2 9/125 (Black) Uni Tube CST OM1 62.5/125 (Black) Uni Tube CST OM2 50/125 (Black) Uni Tube CST OM3 50/125 (Black)	Part Number 002-005-014-xx 002-005-008-xx 002-005-007-xx
Uni Tube CST OM3 50/125 (Black) Uni Tube CST OM4 50/125 (Black)	002-005-040-xx 002-005-009-xx

xx = number of fibres

3.0 mm

1.3 +/- 0.2 mm 7.9 +/- 0.4 mm

IEC 60332-1, IEC 61034 and IEC 60754

Free Cut to Length Service

Connectix hold extensive stock of multi purpose uni-tube distribution cables. We offer a fast turnaround cut to length service providing lengths to your exact requirements. This service is free of charge, and all orders from stock can be available for next day delivery.



