



150Mbps Mini Wireless N USB Adapter TEW-648UB(V1.0R)

The 150Mbps Mini Wireless N USB Adapter (model TEW-648UB) connects a laptop or desktop computer to a wireless n network at up to 6x the speed and 3x the coverage of a wireless g connection.

Enjoy proven wireless n speed and reliability in an ultra compact design that is slightly larger than a US penny.

Setup is a breeze with one-touch Wi-Fi Protected Setup (WPS) technology. Advanced wireless encryption protects your valuable data. Wi-Fi Multimedia (WMM) Quality of Service (QoS) prioritizes important video, audio and gaming traffic. Seamlessly stream video, download files, play games and talk online with this ultra compact wireless n adapter.

FEATURES

- Wi-Fi compliant with IEEE 802.11n standards
- One-touch setup with Wi-Fi Protected Setup (WPS) support
- High speed USB 2.0 interface
- Backwards compatible with IEEE 802.11g and IEEE 802.11b devices
- Supports Ad-Hoc (Client-Client) and Infrastructure (AP-Client) Mode
- Maximum reliability, throughput and connectivity with automatic data rate switching
- Supports 64/128-bit WEP, WPA/WPA2-RADIUS and WPA-PSK/WPA2-PSK
- Low interference and high susceptibility provide reliable performance
- Wi-Fi Multimedia (WMM) Quality of Service (QoS) supported
- Compatible with Windows XP and Vista operating systems
- Easy user setup and intuitive diagnostic utility
- Coverage of up to 50 meters indoor (160 feet) and 100 meters outdoor (320 feet) *
- 3-year limited warranty

150Mbps Mini Wireless N USB Adapter

TEW-648UB[V1.0R]

SPECIFICATIONS

Hardware	
Interface	• USB 2.0
Standards	• IEEE 802.11b, IEEE 802.11g and IEEE 802.11n (draft 2.0)
LED Indicator	• Activity, WPS
WPS Button	• Enables WPS connection
Power Consumption	• Receive mode: 200mA (max) ; Transmit mode : 300mA (max)
Supported OS	• Windows XP(32/64-bit)/Vista (32/64-bit)
Dimensions (LxWxH)	• 33.9 x 17 x 7mm (1.3 x 0.66 x 0.27in)
Weight	• 3g (0.1oz)
Temperature	• Operating: 0° ~ 40° C (32° ~ 104° F); Storage: -10° ~ 70° C (14° ~ 158° F)
Humidity	• 10% ~ 95% max (non-condensing)
Certifications	• CE, FCC
Wireless	
Modulation	• DBPSK/DQPSK/CCK/OFDM (BPSK/QPSK/16-QAM/64-QAM)
Antenna	• Built-in on board antenna
Frequency	• 2.412 ~ 2.484 GHz
Data Rate (auto fallback)	• 802.11b: 11Mbps, 5.5Mbps, 2Mbps, and 1Mbps • 802.11g: 54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 9Mbps and 6Mbps • 802.11n: up to 150Mbps
Output Power	• 802.11b: 15dBm (typical) • 802.11g: 14dBm (typical) • 802.11n: 12dBm (typical)
Receiving Sensitivity	• 802.11b: -84dBm (typical) at 11mpbs • 802.11g: -68dBm (typical) at 54Mbps • 802.11n: -65dBm at 150Mbps
Encryption	• 64/128-bit WEP, WPA/WPA2-Radius, WPA-PSK/WPA2-PSK
Channels	• 1~ 11 (FCC), 1~13 (ETSI)

*Maximum wireless signal rates are referenced from IEEE 802.11 theoretical specifications. Actual data throughput and coverage will vary depending on interference, network traffic, building materials and other conditions.



150Mbps Mini Wireless N USB Adapter TEW-648UB[V1.0R]

NETWORKING SOLUTIONS

150Mbps Mini Wireless N USB Adapter (TEW-648UB)



PACKAGE CONTENTS

- TEW-648UB
- CD-ROM (Utility and Driver)
- Multi-Language Quick Installation Guide

RELATED PRODUCTS

TEW-651BR	150Mbps Wireless N Home Router
TEW-642EC	Wireless N Express Card
TEW-643PI	Wireless N PCI Adapter

ORDERING INFORMATION

TRENDnet®

20675 Manhattan Place, Torrance, CA 90501 USA

Tel: 1-310-961-5500

Fax: 1-310-961-5511

Web: www.trendnet.com

Email: sales@trendnet.com

To Order Please Call:

1-888-326-6061

