



# 4000 Series Vertical Outlet

## Features & Benefits

- High Density, single gang unit
- Available in a 2 or 4 port version
- Enhanced Category 5 performance
- No protruding leads
- Designed for direct wall mounting
- Custom logo service available

## Specifications

Width	87 mm
Depth	27 mm
Height	87 mm
Material	ABS thermoplastic resin, with grade UL94 VO at 1.5 mm flame retardancy
Finish	High gloss
IDC Colour	Code IDC colour code to T568B
IDC Blocks	Industry standard IDC blocks
PCB	1.6 mm double sided PTH boards
Conforms	to ANSI/TIA-568-C Enhanced Category 5 Specification

The Connectix 4000 Series offers Enhanced Category 5 performance in a High-Density package.

The Connectix 4000 Series is extremely quick and easy to install; just attach the base plate, snap in the PCB, punch down the cables and install the cover. Gone are the problems of installing modules into a faceplate and pushing excess wires into a back box.

The 4000 Series Outlets have been designed for direct wall mounting with top entry mini trunking. In addition, they fit on a standard back box to provide maximum mounting flexibility. The position of the sockets on the Vertical Outlet allow for a compact installation without protruding leads.

## Ordering Information

Product Description	Part Number
CCS Cat 5e 4 Way Vertical Wall Outlet	008-001-011-01
CCS Cat 5e 2 Way Vertical Wall Outlet	008-001-011-03

