



### Features & Benefits

- Fully shielded for signal protection
- Shielding prevents contaminant noise from entering the cabling system
- Individually tested up to 250 MHz
- Available from stock in lengths from 0.5 to 5 metres
- Fully conforms to ANSI/TIA-568-C

### Specifications

|             |                               |
|-------------|-------------------------------|
| Plug        | High performance modular plug |
| Cable       | Category 6 stranded cable     |
| Conforms to | ANSI/TIA-568-C                |

### Ordering Information

| Colour | Length | Product Number  | Length | Product Number  |
|--------|--------|-----------------|--------|-----------------|
| Grey   | 0.5 m  | 003-4B5-005-01B | 1 m    | 003-4B5-010-01B |
| White  | 0.5 m  | 003-4B5-005-02B | 1 m    | 003-4B5-010-02B |
| Blue   | 0.5 m  | 003-4B5-005-03B | 1 m    | 003-4B5-010-03B |
| Green  | 0.5 m  | 003-4B5-005-04B | 1 m    | 003-4B5-010-04B |
| Red    | 0.5 m  | 003-4B5-005-05B | 1 m    | 003-4B5-010-05B |
| Yellow | 0.5 m  | 003-4B5-005-06B | 1 m    | 003-4B5-010-06B |
| Orange | 0.5 m  | 003-4B5-005-07B | 1 m    | 003-4B5-010-07B |
| Purple | 0.5 m  | 003-4B5-005-08B | 1 m    | 003-4B5-010-08B |
| Black  | 0.5 m  | 003-4B5-005-09B | 1 m    | 003-4B5-010-09B |
|        |        |                 |        |                 |
| Grey   | 2 m    | 003-4B5-020-01B | 3 m    | 003-4B5-030-01B |
| White  | 2 m    | 003-4B5-020-02B | 3 m    | 003-4B5-030-02B |
| Blue   | 2 m    | 003-4B5-020-03B | 3 m    | 003-4B5-030-03B |
| Green  | 2 m    | 003-4B5-020-04B | 3 m    | 003-4B5-030-04B |
| Red    | 2 m    | 003-4B5-020-05B | 3 m    | 003-4B5-030-05B |
| Yellow | 2 m    | 003-4B5-020-06B | 3 m    | 003-4B5-030-06B |
| Orange | 2 m    | 003-4B5-020-07B | 3 m    | 003-4B5-030-07B |
| Purple | 2 m    | 003-4B5-020-08B | 3 m    | 003-4B5-030-08B |
| Black  | 2 m    | 003-4B5-020-09B | 3 m    | 003-4B5-030-09B |
|        |        |                 |        |                 |
| Grey   | 4 m    | 003-4B5-040-01B | 5 m    | 003-4B5-050-01B |
| White  | 4 m    | 003-4B5-040-02B | 5 m    | 003-4B5-050-02B |
| Blue   | 4 m    | 003-4B5-040-03B | 5 m    | 003-4B5-050-03B |
| Green  | 4 m    | 003-4B5-040-04B | 5 m    | 003-4B5-050-04B |
| Red    | 4 m    | 003-4B5-040-05B | 5 m    | 003-4B5-050-05B |
| Yellow | 4 m    | 003-4B5-040-06B | 5 m    | 003-4B5-050-06B |
| Orange | 4 m    | 003-4B5-040-07B | 5 m    | 003-4B5-050-07B |
| Purple | 4 m    | 003-4B5-040-08B | 5 m    | 003-4B5-050-08B |
| Black  | 4 m    | 003-4B5-040-09B | 5 m    | 003-4B5-050-09B |

Connectix Category 6 FTP Patch Leads are designed to exceed the performance requirements of the Category 6 Specification.

The Connectix Cat 6 Patch Leads are made from Category 6 stranded cable and are terminated using high performance modular plugs. The fully shielded patch leads increase signal isolation and prevent contaminant noise from entering a cabling system.

Each lead is individually factory tested to the standard to ensure true Category 6 compatibility.

We stock a variety of lead lengths, each available in a number of different colours.

