

Copper Cabling Solutions

Category 6 UTP LJ6C Module

The Connectix LJ6C Compact Module range is designed to provide one of the shallowest outlets on the market. They are the ideal solution wherever back box depth is a problem. LJ6C Modules are ideal for use in floor boxes, or any application that has an industry standard LJ6C aperture.

Single and dual gang faceplates are available for up to four LJ6C modules in addition to panels suitable for Ackerman Floor boxes. Their attractive high gloss finish and easy to use labelling system makes them popular with both installers and users alike.

Installation is made easy with individual colour codes and the use of industry standard IDCs. Connectix LJ6C Modules offer extended PowerSum characteristics and exceed the ANSI/TIA-568-C & C.2 specifications. When combined with Connectix Patch Panels and Cable, the link will perform well more than the stated Specification.

Features & Benefits

- Shallow design requires minimal back-box depth
- Industry standard LJ6C size
- Industry standard IDCs
- Individually QA tested
- Interchangeable with other LJ6C modules and blanks
- 25 Year System Warranty Available



Product Specifications	
Width	25mm
Depth	21mm
Height	38.5mm
Back-box depth	20mm with panel 15mm with faceplate
Mounting Hole	22.3mm x 36.7mm
Panel Thickness	2.0mm Max
Material	Flame retardant polycarbonate/ABS thermoplastic resin
Finish	High gloss
IDC Labels	Colour coded to T568B
Sockets	Unshielded RJ45
IDC Blocks	4-way industry standard IDC blocks
Conforms to	ANSI/TIA-568-C

Ordering Information	
Product Description	Part Number
Cat 6 UTP LJ6C Module	008-000-001-10